



eWORKER 25.5-90



Maximum Load Capacity: 5,511 Lbs
Maximum Lift Height: 15' 7"
Maximum Reach: 8' 5"
Load Capacity at Max. Reach: 1,984 Lbs
Load Capacity at Max. Lift: 3,307 Lbs

PERFORMANCE

Unladen Weight (lbs)	10,913
Maximum Load Capacity (lbs)	5,511
Lift Height (ft)	15' 7"
Maximum Reach (ft)	8' 5"
Load Capacity at Max. Lift Height (lbs)	3,307
Load Capacity at Max. Reach (lbs)	1,984
Height - Maximum Load Capacity (ft)	11' 1"
Reach at Maximum Load Capacity (ft)	11' 2"
Boom Sections	2

POWERTRAIN

Motor	Electrical
Battery (type and V)	Lead-acid-48V
Normal Capacity	960 Ah
Emissions	No emissions
Maximum Power (kW/Cv)	66/90
Maximum Speed (mph)	15
Traction	4WD
Autonomy (hours)	8
Recharge Time at 220 V (hours)	9
Recharge Voltage	220V/400V
Battery Charger	●
Brakes	Front Wet
Automatic Parking Brake	●

HYDRAULIC

Hydraulic Pump	Load Sensing
Delivery/Pressure (psi-gal/min)	3,045-11
Hydraulic Outlet on Top of Boom	●
Rear Hydraulic	●

● Standard ● Optional

DIMENSIONS

A(ft)	10' 9"	E(ft)	9' 6"	P(ft)	6' 5"
B(ft)	2' 5"	F(ft)	0' 9"	R(ft)	10' 7"
C(ft)	6' 9"	H(ft)	5' 0"	S(ft)	8' 9"
D(ft)	1' 2"	M(ft)	2' 5"	T(ft)	2' 2"

The technical data and other information in this document are not binding. We reserve the right to modify our products without prior notice as part of our policy of continuous improvement

CAB

Closed Cab	●
FOPS LEV I Cab	●
ROPS Cab	●
Controls	Electronic Joystick
Reverse Shuttle	Dual Reverse

CONFIGURATION

Battery Fast Replacement	●
Tac-lock	●
Work Lights on Cab	●
Sun-shade in the cab	●
Two floating forks	●
Boom Suspension	●
Two steering wheels	●
Standard tires	10,0/75-15,3
Optional tires	7,5R15 31X15,5-15
Pre-arrangement for aerial work platform	●
Tractor type approval	●
4 Wheel Drive	●

