



# MF44.9 CS



**Maximum Load Capacity:** 9,700 Lbs  
**Maximum Lift Height:** 28' 8"  
**Maximum Reach:** 19' 0"  
**Load Capacity at Max. Reach:** 2,200 Lbs  
**Load Capacity at Max. Lift:** 9,700 Lbs



PERFORMANCE	
Unladen Weight (lbs)	21,010
Maximum Load Capacity (lbs)	9,700
Lift Height (ft)	28, 8"
Maximum Reach (ft)	19, 0"
Load Capacity at Max. Lift Height (lbs)	9,700
Load Capacity at Max. Reach (lbs)	2,200
Boom Side-Shift (in)	-
Frame Leveling	± 8°
Boom Sections	3

POWERTRAIN	
Engine	FPT
Displacement/Cylinders	4.5/4
Engine Power (HP)	170
Reversible Fan	●
Maximum Speed (mph)	25
Fuel Tank Capacity (gal)	37
AdBlue Tank Capacity (gal)	-
CVtronic Transmission	CVtronic
EPD	Plus
Axles	Axial
Reducers	Epicyclic
Brakes	Dry Discs
Automatic Parking Brake	●

HYDRAULIC	
Hydraulic Pump	LS + FS
Delivery/Pressure (gal/min-psi)	40/3046
Hydraulic Oil Tank Capacity (gal)	26
Auxiliary Hydraulic Service on Boom	●
Rear Service Line	4 - ●

● Standard    ● Optional

DIMENSIONS			
Width (ft)	7'8"	Length (ft)	18'0"
Height (ft)	8'2"	Wheelbase (ft)	9'6"
Ground Clearance	1'5"	Turning Radius Over Tires	13'5"

The technical data and other information in this document are not binding. We reserve the right to modify our products without prior notice as part of our policy of continuous improvement

CAB	
Cab Finishing	Premium
MCDC	Full
FOPS II Cab	●
ROPS Cab	●
Controls	Electromechanical Joystick
Reverse Shuttle	Dual Reverse

CONFIGURATION	
Hydropneumatic Suspension CS Merlo	●
Hydropneumatic Suspension BSS Merlo	○
Hydropneumatic Suspension EAS Merlo	-
Work lights on cab	●
Sun-shade in the cab	●
Tac-lock	●
Pre-arrangement for aerial work platform	○
Two floating forks	●
Pedal Inching-Control	●
Permanent four-wheel drive	●
4 Wheel Drive	●
3 Steering Modes	●
Standard tires	500/70-R24"
Hydraulically controlled stabilizers	-
Turret rotation	-
Tractor type approval	○
PTO	135HP    540/1000
3-point rear linkage	●

